

# FSW-2104

## 4-Port 10/100Base-TX and 100Base-FX Switch



The FSW-2104 provides a low cost solution for non-managed Ethernet fiber switches. The FSW-2104 is a 4-port 10/100Base-TX plus 1-port 100Base-FX Fast Ethernet switch. It is designed for small workgroup applications that require a long distance connection to the backbone, such as between buildings, offices, or within a campus location. FSW2104 provide full-duplex capability on each auto-negotiating port, for enhanced performance. A wide range of transceiver selection provides fiber connection with SC, FC or ST type connectors in multimode or single mode and at distance from 2 to 120km as well as BiDi (single fiber) at distances of 20, 40, 60, or 80km.

### Features


- 4-Port 10/100Base-TX to 100Base-FX
- Auto-Negotiation
- Auto MDI / MDIX
- Forward 1552 bytes (Max.) packets
- Supports 1K MAC address
- 512k bits packet buffer memory
- Supports broadcast storm protection

### Specifications

Optical Interface		
Connector	1x9 (SC, ST)	
Data rate	100Mbps	
Duplex mode	Full duplex	
Fiber	MM 50/125µm, 62.5/125µm.	
	SM 9/125µm	
Distance	MM 2km, SM 15/30/50/80/120km	
	WDM 20/40/60/80km	
Wavelength	MM 1310nm, SM 1310,1550nm	
	WDM 1310Tx/1550Rx (type A)	
	1550Tx/1310Rx (type B)	
Electrical Interface		
Connector	RJ-45	
Data rate	10Mbps, 100Mbps	
Duplex mode	Half / Full duplex	

<b>Electrical Interface</b>	Cable	10Base-T Cat.3, 4, 5, UTP 100Base-TX Cat.5, 5e or higher
<b>Standards</b>	IEEE 802.3, IEEE 802.3u	
<b>Indications</b>	LED (FX Link, TX SPD, TX Link/Act)	
<b>Power Input</b>	Card	: 5 VDC
	Standalone	: AC, DC options
<b>Power Consumption</b>	< 4W	
<b>Dimensions</b>	138 × 77 × 28mm (D × W × H)	
<b>Weight</b>	450g	
<b>Temperature</b>	0 ~ 50°C (Operating), 0 ~ 70°C (Storage)	
<b>Humidity</b>	10 ~ 90% non-condensing	
<b>Certification</b>	CE, FCC, RoHS compliant	
<b>MTBF</b>	65,000 hrs	

### Application



### Ordering Information

Model Name	Description
FSW-2104	4-Port 10/100Base-TX to 100Base-FX Managed Switch

Connector Type	Connectivity Distance
SC	002: 2km 015: 15km 030: 30km 050: 50km 080: 80km 120:120km 20A: WDM 20km A type 20B: WDM 20km B type 40A: WDM 40km A type 40B: WDM 40km B type 60A: WDM 60km A type 60B: WDM 60km B type 80A: WDM 80km A type 80B: WDM 80km B type

Connector Type Connectivity Distance  
**FSW - 2104** - □□□□□  
 Example: **FSW - 2104 - SC002**

Specifications & design are subject to change without prior notice. Please visit CTC Union website for more details.