

Ethernet Switch Comparison Table



	<i>MSW-4424A/S</i>	<i>MSW-202</i>	<i>MSW-404/404S</i>	<i>GSW-3420FM</i>	<i>GSW-3424M1</i>	<i>GSW-3216M1</i>	<i>GSW-3208M1</i>	<i>GSW-3216MP</i>	<i>GSW-3208MP</i>	<i>GSW-2008MS</i>	<i>GSW-1005MS</i>
Service port	10/100/1000Base-T RJ45	2	4		20	16	8	16	8	8	5
	100/1000Base-X SFP slot	24			20						
Uplink port	Gigabit combo port			4	4						
	100/1000Base-X SFP slot	2	4			2	2	2	2	2	1
	1G/10Gbase-X SFP+ slot	4									
IEEE 802.3af/at PoE port								16	8		
Power Supply	External power adaptor									V	V
	AC power module	100V~240VAC	100V~240VAC	100V~240VAC	100V~240V	100V~240V	100V~240V	100V~240V	100V~240VAC	100V~240VAC	
	DC power module	-36V~-60V (-48VDC power) -9~-32V (-24VDC power)	18 ~ 72VDC	-36V~-60V (-48VDC power)	-36V~-72V (-48VDC power)	-36V~-72V (-48VDC power)	-36V~-72V (-48VDC power)	-36V~-72V (-48VDC power)			
	Dual power options	V	V	V	V						
Network Management	SNMP (v1/v2c/v3)	V	V	V	V	V	V	V	V	V	V
	OAM (IEEE 802.3ah/802.1ag/ITU-T Y.1731)	V	V	V							
MEF Certification	CE 2.0(plan)	CE 2.0(plan)	CE 2.0(plan)								
Timing Synchronization	ITU-T G.8262 Sync. Ethernet	V (MSW-4424S)		V (MSW-404S)							
	IEEE 1588v2	V (MSW-4424S)		V (MSW-404S)							
IPv6 support	V	V	V	V	V	V	V	V	V	V	V
Cable Tray option										V	V