



FRM220A-GSW/SNMP

Gigabit Ethernet Aggregate Switch Card

The FRM220A incorporates a 24+4 Gigabit Ethernet Switch. Twenty ports supply each slot of the 2U 20-slot chassis with an electrical gigabit Ethernet uplink with the remaining four electrical gigabit ports accessible via the rear of the chassis. The additional four ports are provided by SFP sockets. All eight Gigabit ports (4+4) are usable without restrictions for uplink aggregate to the Ethernet Metropolitan Area Network (E-MAN). The FRM220A-GSW/SNMP card transmits Ethernet between the subscriber equipment (bridge/ modem or network interface card) and the E-MAN. The card provides a user-networking interface with Ethernet packets. This card is capable of providing high bandwidth for assembling Ethernet traffic. The FRM220A-GSW/SNMP card is not only the system aggregate/trunk module, but also the system's control module, providing OAM Management functions.

Features

- Provides chassis aggregation via 4x1000Base-X SFP uplink slots (FRM220A-GSW/SNMP)
- Fiber optical ports supports ring or chain topology
- Built-in gigabit Ethernet interface to link with each slot of FRM220A chassis
- Provides Web, Telnet, SNMP management interface
- Supports IEEE802.1D/802.1w/802.1s for ring protection on the trunk interfaces
- Supports IEEE 802.1Q tagged VLAN and IEEE 802.1ad Q-in-Q application

Specifications

Trunk Interface	4x10/100/1000Base-T plus 4x1000Base-X/2500Base-X GbE switch trunk card (FRM220-GSW/SNMP) Supports full-duplex mode for 1000Mbps (FRM220A-GSW/SNMP)
Capacity	Supports up to 20 service cards
Temperature	0~60°C (Operating), -10~70°C (Storage)
Humidity	5~90% non-condensing
Certification	CE, FCC, RoHS compliant

Physical Specifications	In-band management	Provides all system OAM functions: software updates, and management system interaction through Ethernet trunk port
	Out-band management	Supports Web, Telnet and SNMP, EMS management
Indications	PWR, FAN, Alarm, STK	
Dimensions	142 x 200 x 26 mm (D x W x H)	
Weight	0.5kg	
MTBF	65,000 hrs	

Ordering Information

Model Name	Type	Description
FRM220A-CH20	Chassis	2U 20-Slot rack mount chassis with 20 line card blank plate
FRM220A-GSW/SNMP	Card	Gigabit Ethernet Aggregate switch card supports web, telnet, SNMP management interface
FRM220A-AC	Power	Chassis power module 100 ~ 240VAC, IEC connector
FRM220A-DC24	Power	Chassis power module 18 ~ 36VDC, 3 pin terminal block
FRM220A-DC48	Power	Chassis power module 36 ~ 72VDC, 3 pin terminal block

FRM220A – ^{Chassis} □□□□
Example: FRM220A – CH20

FRM220A – ^{Card} □□□□ / □□□□
Example: FRM220A – GSW/SNMP