

Industrial Managed GbE Switch



IGS+404SM

4x 10/100/1000Base-T+
4x 100/1000Base-X SFP

This IGS+404SM is managed industrial grade gigabit switches with 4 10/100/1000Base-T ports and 4 Gigabit/Fast Ethernet SFP ports that provide stable and reliable Ethernet transmission. The switches support a variety of Ethernet functions, including STP/RSTP/MSTP/ ITU-T G.8032 ERPS and multiple μ -Ring for redundant cabling, layer 2 Ethernet IGMP, VLAN, QoS, Security, IPv6, bandwidth control, port mirroring, cable diagnostic and Green Ethernet. Housed in rugged DIN rail or wall mountable enclosures, these switches are designed for harsh environments, such as telecom network, industrial network, security automation applications, intelligent transportation systems (ITS) and are also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications. Standard operating temperature range models (-10 to 60°C) and wide operating temperature range models (-40 to 75°C) fulfill the special needs of industrial automation applications.

Feature

- 4x 10/100/1000Base-T RJ-45 and 4x 100/1000Base-X SFP Fiber
- Redundant dual DC input power 12/24/48VDC (9.6~60VDC)
- Supports negative power input with isolated RS-232 console port (for example in telecom system)**
- UL60950-1, CE, FCC, Rail Traffic EN50121-4, Traffic control NEMA TS2 certified
- Industrial grade EMS, EMI, EN61000-6-2, EN61000-6-4 certified
- 2.25K VDC Hi-pot isolation protection for Ethernet ports and power**
- Cable diagnostic, Measuring cable normal or broken point distance
- Supports Green Ethernet IEEE802.3az EEE (Energy Efficient Ethernet) management to optimize the power Consumption
- STP, RSTP, MSTP, ITU-T G.8032 Ethernet Ring Protection Switching (ERPS) for redundant cabling
- Provides 5 instances that each can support μ -Ring, u-Chain or Sub-Ring type for flexible uses. Supports up to 5 rings in one device
- μ -Ring for Redundant Cabling, recovery time<10ms in 250 devices
- DHCP Server/Client/Relay/Snooping/Snooping option 82/Relay option 82
- QoS, Traffic classification QoS, CoS, bandwidth control for Ingress and Egress, Storm Control, DiffServ
- IEEE802.1q VLAN, MAC based VLAN, IP subnet based VLAN, Protocol based VLAN, VLAN translation, GVRP, MVR
- Dynamic IEEE 802.3ad LACP Link Aggregation, Static Link Aggregation
- IGMP snooping V1/V2/V3, IGMP Filtering/ Throttling, IGMP query, IGMP proxy reporting, MLD snooping V1/V2
- Security : Port based and MAC based IEEE802.1X, RADIUS, ACL, TACACS+, HTTP/HTTPS, SSL/SSH v2
- Software upgrade via TFTP and HTTP, redundant firmware to avoid in case of upgrade failure
- Supports IEEE1588 PTP V2 for precise time synchronization to operate in Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master, Slave mode by each port
- RMON, MIB II, Port mirroring, Event syslog, DNS, NTP, SNMP, IEEE802.1ab LLDP
- Supports IPv6 Telnet server /ICMP v6
- CLI, Web based management, SNMP v1/v2c/v3, Telnet server for management
- Provides SmartConfig for quick and easy mass configuration tool
- Supports SmartView for Centralized management
- Supporting Central EMS for management of up to 50 SmartView Server, and maximum up to 25,000 device

Specifications

Standard	IEEE 802.3	10Base-T 10Mbit/s Ethernet	Data Processing	Store and Forward											
	IEEE 802.3u	100Base-TX, 100Base-FX, Fast Ethernet		Flow Control	IEEE 802.3x for full duplex mode Back pressure for half duplex mode										
	IEEE 802.3ab	1000Base-T Gbit/s Ethernet over twisted pair			Network Connector	4x 10/100/1000Base-T RJ-45 + 4x 100/1000Base-X SFP connector									
	IEEE 802.3z	1000Base-X Gbit/s Ethernet over Fiber-Optic				RJ-45 UTP port support Auto negotiation speed, Auto MDI/MDI-X function, SFP port support dual speed with DDMI									
	IEEE 802.1d	STP (Spanning Tree Protocol)				Console	RS-232 (RJ-45)								
	IEEE 802.1w	RSTP (Rapid Spanning Tree Protocol)					Isolated RS-232 port grounding for negative power system, or telecom application								
	IEEE 802.1s	MSTP (Multiple Spanning Tree Protocol)					Network Cable	UTP/STP above Cat. 5e cable							
	ITU-T G.8032 / Y.1344	ERPS (Ethernet Ring Protection Switching)						EIA/TIA-568 100-ohm (100m)							
	IEEE 802.1Q	Virtual LANs (VLAN)						Protocols	CSMA/CD						
	IEEE 802.1X	Port based and MAC based Network Access Control, Authentication							Reverse Polarity Protection	Present					
	IEEE802.3ac	Max frame size extended to 1522Bytes.								Overload Current Protection	Present				
	IEEE 802.3ad	Link aggregation for parallel links with LACP(Link Aggregation Control Protocol)									CPU Watch Dog	Present			
	IEEE 802.3x	Flow control for Full Duplex										Power Supply	Redundant Dual input power (Removable Terminal Block)		
	IEEE 802.1ad	Stacked VLANs, Q-in-Q											DC 12/24/48V (9.6~60VDC)		
	IEEE 802.1p	LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization											Support negative voltage input power for telecom		
	IEEE 802.1ab	Link Layer Discovery Protocol (LLDP)											Power Consumption	Input Voltage (V)	Power consumption (Watt)
	IEEE 802.3az	EEE (Energy Efficient Ethernet)												12V	7.7
	VLAN ID	4094 IEEE802.1Q VLAN VID												24V	8
	Switch Architecture	Back-plane (Switching Fabric): 16Gbps Full wire-speed												48V	9.2

LED	Per unit: Power 1 (Green), Power 2 (Green), Fault (Amber), CPU Act (Green), Ring Master (Yellow) Per RJ-45 port: 10/100 Link/Active (Green) 1000 Link/Active (Amber) SFP Fiber Per port: Link/Active (Green)
Jumbo Frame	9.6KB
IEEE802.3ac	Max frame size extended to 1522Bytes (allow Q-tag in packet)
MAC Address Table	8K
Memory Buffer	512K Bytes for packet buffer
Warning Message	System Syslog, SMTP/ e-mail event message, alarm relay
Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC
Removable Terminal Block	Provide 2 redundant power, alarm relay contact, 6 Pin
Operating Temperature	-10 ~ 60°C (IGS+404SM) -40 ~ 75°C (IGS+404SM-E)
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40 ~ 85°C
Housing	Rugged Metal, IP30 Protection, Fanless
Dimensions	106 x 62.5 x 135 mm (D x W x H)
Weight	650g
Installation Mounting	DIN Rail mounting , or wall mounting (Optional)
MTBF	861,962 Hours (MIL-HDBK-217)
Warranty	5 years

Software Specifications

Topology	
VLAN	IEEE 802.1q VLAN, up to 4094 802.1Q VLAN VID IEEE 802.1q VLAN, up to 4094 Groups IEEE 802.1ad Q-in-Q MAC-based VLAN, up to 256 entries IP Subnet-based VLAN, up to 128 entries Protocol-based VLAN (Ethernet, SNAP, LLC), up to 128 entries VLAN Translation, up to 256 entries GVRP (GARP VLAN Registration Protocol) MVR (Multicast VLAN Registration)
Link Aggregation (Port Trunk)	Static (Hash with SA, DA, IP, TCP/UDP port), up to 5 trunk group Dynamic (IEEE 802.3ad LACP), up to 5 trunk group
Spanning Tree	IEEE802.1d STP IEEE802.1w RSTP IEEE802.1s MSTP
Multiple μ-Ring	up to 5 instances that each supports μ-Ring, u-Chain or Sub-Ring type for flexible uses, and maximum up to 5 Rings. Recovery time <10ms The maximum number of devices allowed in a Ring supported ring is 250.
Loop Protection	Present
ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection)	Recovery time <50ms Single Ring, Sub-Ring, Multiple ring topology network
QoS Features	
Class of Service	IEEE802.1p 8 active priorities queues for per port
Traffic Classification QoS	IEEE802.1p based CoS IP Precedence based CoS IP DSCP based CoS QCL(QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI QCE(QoS Control Entry): Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number
Bandwidth Control for Ingress	Rate in steps :1 kbps / Mbps / fps / kfps Range : 100 kbps to 1Gbps / 1fps to 3300kfps Rate Unit : bit or frame
Bandwidth Control for Egress	Rate in steps : 1 kbps / Mbps Range : 100 kbps to 1Gbps Rate Unit : bit Per queue / Per port shaper
DiffServ (RF 2474) Remarking	
Storm Control	for Unicast, Broadcast, Multicast

Certification	
EMC	CE
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE EN55022 Class A
Railway Traffic	EN50121-4
Immunity for Heavy Industrial Environment	EN61000-6-2
Emission for Heavy Industrial Environment	EN61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (Burst) Level 3, Criteria A EN61000-4-5 (Surge) Level 3, Criteria B EN61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A
Safety	UL60950-1
Hi pot protection	DC 2.25KV for power to chassis ground, Ethernet ports to chassis ground
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

IP Multicasting Features	
IGMP / MLD Snooping	IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2 Port Filtering Profile Throttling, Fast Leave Maximum Multicast Group : up to 1022 entries Query / Static Router Port
Security Features	
IEEE 802.1X	Port-Based MAC-Based
ACL	Number of rules : up to 256 entries for L2 / L3 / L4
RADIUS authentication & accounting	
TACACS+ authentication & accounting, TACACS+ 3.0	
HTTPS, HTTP	
SSL / SSH v2	
User Name Password Authentication	Local Authentication Remote Authentication (via RADIUS / TACACS+)
Management Interface Access Filtering	Web, Telnet / SSH , CLI RS-232 console
Management Features	
CLI	Cisco® like CLI
Web Based Management	
Telnet	Server
SNMP	V1, V2c, V3
SW & Configuration Upgrade	TFTP, HTTP Redundant firmware in case of upgrade failure
RMON	RMON I (1, 2, 3, 9 group), RMON II
MIB	RFC1213 MIB II, Private MIB
UPnP	
DHCP	Server, Client, Relay, Snooping Snooping option 82 Relay option 82
IP Source Guard	
Port Mirroring	
Event Syslog	Syslog server (RFC3164) (Support 1 server)
Warning Message	System syslog, e-mail, alarm relay
DNS	Client, Proxy


Industrial Managed GbE Switch

IEEE1588 PTP V2	Support 5 operating mode in each port : Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master, Slave
NTP, SNTP	Client
LLDP (IEEE 802.1ab)	Link Layer Discovery Protocol LLDP-MED
IPv6 Features	
IPv6 Management	Telnet Server/ICMP v6
SNMP over IPv6	


HTTP over IPv6	
SSH over IPv6	
IPv6 Telnet Support	
IPv6 NTP, SNTP	Client
IPv6 TFTP Support	
IPv6 QoS	
IPv6 ACL	Number of rules: up to 256 entries L2 / L3 / L4

Application

► Figure : Application Example




Dimension



Ordering Information

Model Name	Managed	Total Port	UTP Port	Fiber Port	Certification					Operating Temperature
			10/100/1000 Base-T	100/1000 Base-X	Railway EN50121-4	NEMATS2	Safety UL60950-1	EN61000-6-2 EN61000-6-4	CE FCC	
IGS+404SM	V	8	4	4 SFP	V	V	V	V	V	-10~60°C
IGS+404SM-E	V	8	4	4 SFP	V	V	V	V	V	-40~75°C

Model Naming Rule



Optional Accessories

Wall mount kit

IND-WMK02	Wall Mount kit (Wide), 184x50mm
-----------	---------------------------------

Package List

- One device of the series
- Console cable (RJ-45 to DB9)
- CD (SmartConfig, MIB file, Manual)
- Quickly installation guide
- Din Rail with screws
- Terminal block
- Protective caps for SFP ports