

Appendix

- FRM220 Standalone Selection Table

Model Name	Slot	NMC Card Slot	Console Port	Adapter Type	Power Built-In Type			Cooling Fan	Fan-less	Power Module
				100~240VAC to 12VDC	100~240VAC	18~72VDC	Dual Power 100~240VAC & 18~72VDC			
CH01	1			✓					✓	12W
CH01-AC	1				✓				✓	12W
CH01-DC	1					✓			✓	12W
CH01-AD	1						✓		✓	12W/12W
CH01M-AC	1		✓		✓				✓	12W
CH01M-DC	1		✓			✓			✓	12W
CH01M-AD	1		✓				✓		✓	12W/12W
CH02	2			✓					✓	30W
CH02M-AC	2		✓		✓			✓		30W
CH02M-DC	2		✓			✓		✓		30W
CH02M-AD	2		✓				✓	✓		30W/30W
CH02M-2-AC	2		✓		✓				✓	12W
CH02M-2-DC	2		✓			✓			✓	12W
CH02M-2-AD	2		✓				✓		✓	12W/12W
CH02/NMC-AC	2	✓			✓			✓		30W
CH02/NMC-DC	2	✓				✓		✓		30W
CH02/NMC-AD	2	✓					✓	✓		30W/30W
CH04A-AC	4	✓			✓			✓		65W
CH04A-DC	4	✓				✓		✓		50W
CH04A-AD	4	✓					✓	✓		65W/50W

How to order

- DIP Switch Configuration Order : CH01 and CH02
- Local Console Management Order : CH01M, CH02M and CH02M-2. "M" means the chassis with Console Management.
- Remote Web / SNMP Management Order : CH02 / NMC, CH04A
- Power Type : AD = AC + DC Power