



SHDTU04bF-ET10RS SHDUT04bAF-ET10RS SHDTU04bCF-ET10RS

G.SHDSL.bis ATM EFM Router

The G.SHDSL.bis ATM EFM Router is 2/4/8wires Ethernet Bridge/Router that complies with G.991.2 standards and has an optional built-in four port 10Base-T /100Base-TX auto-negotiation and auto-MDIX switch. The G.SHDSL.bis ATM EFM Router provides multi-rate 2-wire / 5.7Mbps or 4-wire / 11.4Mbps and 8-wire / 22.78Mbps payload rates over existing single or two pair copper wire. The G.SHDSL.bis ATM EFM Router is designed not only to optimize the service bit rate from central office to customer premises but also integrates high-end Bridging/ Routing EFM bonding capabilities with advanced functions such as virtual server mapping and VPN pass through. The G.SHDSL.bis ATM EFM Router allows customers to leverage the latest in broadband technologies to meet their growing data communication needs. In bridge mode, the four switching ports may be configured for IEEE802.1Q VLAN or port based VLAN applications. The modem can be configured in either central or client mode providing a point-to-point solution.

Feature

- Supports Ethernet over ATM over SHDSL
- Full ATM protocol stack implementation over G.SHDSL.bis
- Adaptive rate installation maximizes data rate based on loop conditions
- Standard ITU G.991.2 (2004) supports improved reach, speed and interoperability compared to conventional G.SHDSL
- Supports point-to-point configurations
- Local management interface via console port
- Intuitive Web based management
- SNMP management with SNMPv1/v2 and MIB II
- Build-in advanced SPI firewall (Firewall routers)
- Efficient IP routing and transparent learning bridge to support broadband Internet services
- VPN pass-through for safeguarded connections
- DMZ host/Multi-DMZ/Multi-NAT; multiple PCs on a LAN with only one IP address
- PPPoA and PPPoE support user authentication with PAP/CHAP/MSCHAP
- Raw and time stamped statistics
- Supports firmware upgrade via web interface
- EFM (Ethernet in the First Mile) bonding per IEEE 802.3-2005;2/4-wire bonding for HDLC per G991.2

Specifications

Interface	WAN	SHDSL.bis: ITU-T G.991.2 (2004) Annex A/B/F/G Support EFM Bonding and SHDSL M-Pair mode Line Code: TC-PAM 16/32/64/128 Data Rate: N x 64 Kbps (N=3~89) using TC-PAM 16/32 Max. 5.696Mbps (1-Pair) Max. 11.392Mbps (2-Pair) Max. 22.78Mbps (4-Pair) N x 64 Kbps (N=3~239) using TC-PAM 64/128 Max. 15.296 Mbps (1-Pair) Max. 30.592 Mbps (2-Pair) Max. 61.184Mbps (4-Pair) Impedance: 135 ohms
	LAN	RJ-45 x 4-Ports 10/100 Base-T Ethernet ports
Serial Console	RS-232(Female) Connector	
Factory Default Reset	Push Button	
LED	Power: (Green)	
	WAN: LINK/ACT (Green), one LED per pair LAN (Port 1 ~ Port 4): LINK/ACT (Green:100M, Orange:10M) ALARM: (Red)	
G.SHDSL	Support G.991.2 / G994.1 standards	
	TC-PAM line modulation	
	Configurable as either server or client mode	
	OAM IEEE 802.3 chapter 57 compliant	
	IEEE 802.3 2BASE-TL (aka 802.3ah) compliant	
	Rate negotiating / Manually rate adaptation configuration	
	Connection Loops: 1 pair (2 wires)	
	Support IPoE	
	Support PPPoE	
	IP (RFC 791) routing is supported	
Routing/Bridge Support	TCP, UDP, ICMP, IGMP v1 and v2, ARP, RIP v1, RIP v2, OSPF, BGP-4	
	Transparent bridging (IEEE 802.1D)	
	PPP BCP (RFC 3185) support	
	IGMP snooping	
ATM Support		Multiple protocols over AAL5 (RFC1483) (Not support IPoA/PPPoA) Only 1 PVC
EFM Support		EFM mode compliant to IEEE 802.3 PPP over Ethernet (RFC2516) Support of OAMPDU information and functionality (ITU-T Y.1731) OAMPDU Event Notification, Variable Request, Variable Response, Loopback Control VLAN base QOS (802.1P/Q), Priority Queue
Internet Access Sharing		NAT (includes multi-to-multi NAT) / SUA, 8192 NAT sessions Port restricted cone NAT SIP ALG pass-through NAT server (Port forwarding) Multi-NAT Dynamic DNS DHCP server/client/relay
Security		User Authentication (PAP, CHAP) with PPP (RFC 1334, RFC 1994) Microsoft CHAP Stateful packet inspection firewall Content filter Prevent Denial of service Access control of service Real-time attack alert and log
Network Management		Web-based Configuration, Command-line interface Password-protected Telnet support SNMP MIB I /MIB II support TFTP & FTP firmware upgrade and configuration backup Dying Gasp

G.SHDSL.bis ATM EFM Router

VPN	IPSec VPN support, 10 VPN tunnels IKE/ Manual Key, DES/ 3DES/AES Encryption MD5/ SHA1 Authentication, FQDN NETBIOS pass-through for IPSec, IPSec VPN keep-alive IPSec NAT Traversal	Others	DNS Proxy UNIX syslog Each Ethernet port can be only tagged or only untagged Application QoS IPv6
Diagnostics Capabilities	The router can perform self-diagnostic tests. These tests check the integrity of the following circuitry: -FLASH memory -SDSL circuitry -RAM -LAN port		

Ordering Information

Model Name	Description
SHDTU04bF-ET10RS	4-Port 10/100Base-TX ATM Bridge / Router w/Firewall (2-wire 5.7Mbps)
SHDTU04bAF-ET10RS	4-Port 10/100Base-TX ATM Bridge / Router w/Firewall (4-wire 11.4Mbps)
SHDTU04bCF-ET10RS	4-Port 10/100Base-TX ATM Bridge / Router w/Firewall (8-wire 22.78Mbps)