



IMC-1000S-PH12

100/1000Base-T to 100/1000Base-X SFP with PoE+ (PSE) Fiber Converter (30 Watts, 12V Booster)



IMC-1000S-PH12 is a family of unmanaged Gigabit Ethernet media converters that support conversion between electrical 10/100/1000Base-T and optical 1000Base-X Ethernet and as PSE (Power Source Equipment) provide PoE+ power over Ethernet. The IMC-1000S-PH12 provides an SFP cage for 100/1000Base-X compatible SFP modules. Housed in rugged DIN rail or wall mountable enclosures, these converters are designed for harsh environments, such as industrial networking, intelligent transportation systems (ITS) and are also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications (See Figure 1).

Features

- Conversion between 10/100/1000Base-T and 100/1000Base-X Fiber cable interface
- Supports dual rate (100/1000) SFP for selectable Fast or Gigabit speed on fiber
- 12/24/48VDC (9.6~57VDC) redundant dual input power with built-in very high efficiency booster (97~99%) to rise up 55 VDC for PoE output
- Regulate PoE output voltage (55VDC) to stabilize PoE device, and guarantee delivery PoE power distance to 100meter (Figure 2)
- Provides IEEE802.3at PoE output (30Watts)
- Supports Remote PD reset by fiber port link down (Figure 3)
- Supports LFPT (Link Fault Pass Through)
- IP30 rugged metal housing and fanless
- Wide operating temperature -20~75°C
- CE, FCC, Railway traffic EN50121-4 certification
- Heavy industrial grade EMS,EMI EN61000-6-2, EN61000-6-4 certification
- Supports Jumbo frame 9K bytes packet

Specifications

Standard	IEEE802.3 10Base-T 10Mbit/s Ethernet IEEE802.3u 100Base-TX, 100Base-FX, Fast Ethernet IEEE802.3ab 1000Base-T Gbit/s Ethernet over twisted pair IEEE802.3z 1000Base-X Gbit/s Ethernet over Fiber-Optic IEEE802.3x Flow Control and Back pressure IEEE802.3at PoE+ (Power over Ethernet enhancement) IEEE802.3af PoE (Power over Ethernet) IEEE802.1q Tag VLAN
RJ45 Ports	10/100/1000Base-T Auto MDI/MDI-X and Auto-Negotiation Function Supports UTP CAT.5e Twisted Pair cable
Fiber Ports	100Base-X or 1000Base-X SFP slot 100Base-X or 1000Base-X set by DIP SW
Data Process Architecture	Store and Forward mode or Pass Through mode Set by DIP SW
Jumbo Frame	9K bytes
Fiber Parameters	Fiber Cable (Multi-mode): 50/125um, 62.5/125um Fiber Cable (Single-mode): 9/125um Wavelength: 1310nm (Multi-mode/Single-mode) Available distance: • SFP, Distance depend on plug-in Fiber Transceiver
Link Fault Pass Through (LFPT)	TX- Fiber: If TX port link down, the media converter will force Fiber port to link down Fiber-TX: If Fiber port link down, the media converter will force TX port to link down
DIP Switch	ON: Disable Alarm For Power Loss OFF: Enable Alarm For Power Loss ON: Disable Alarm For Port Link-Failure OFF: Enable Alarm For Port Link-Failure ON: LFPT Enable, OFF: LFPT Disable Data process Architecture : ON : Pass through mode OFF : Store and Forward Switch mode Fiber Speed: OFF: 1000Base-X ON: 100Base-X PoE Output: OFF: Enable PoE output ON: Disable PoE output Remote PD reset (Figure 3) Off : Disable Remote PD reset On: Enable Remote PD reset by fiber port link down

Connector and Pin Assignment	SFP Slot RJ-45 Socket: CAT.5e (10/100/1000Mbps) Twisted Pair cable Auto MDI/MDI-X and Auto-Negotiation Function Support RJ-45 Port support IEEE 802.3at/af End-Span, Alternative A mode.																									
Connector and Pin Assignment	PoE (V+): RJ-45 pin 1, 2. PoE (V-): RJ-45 pin 3, 6. Data (1,2,3,6,4,5,7,8)																									
LED	Per Unit :Power 1 (Green) ,Power 2 (Green) ,Fault (Amber) . Fiber LNK/ACT (Green): ON: Connected to network, OFF: Not connected to network , BLK: Receive /Transmit Data Fiber Speed: Yellow : 1000Base-X, Green : 100 Base- X RJ-45 Port: Speed: 10 (OFF), 100 (Green), 1000 (Yellow) LNK/ACT for RJ45(Green): ON: Connected to network, OFF: Not connected to network, BLK: Networking is active PoE Status (Green): Flash: PoE Fault (Over-load or short), ON: PoE normal working, OFF : PoE No Power output																									
Reverse Polarity Protection	Supported for Power Input																									
Overload Current Protection	Supported																									
Power Supply	12/24/48VDC (9.6~57VDC), Redundant power with polarity reverse protect function and removable terminal block Built-in very high efficiency booster(97~99%) to rise up 55 VDC for PoE output Regulated PoE output voltage (55VDC) to stabilize PoE device, and guarantee delivery PoE power distance to 100meter (Figure 2)																									
PoE Power budget	30W																									
Power Consumption	<table border="1"> <thead> <tr> <th colspan="5">Power consumption & Boost efficiency</th> </tr> <tr> <th>Input Voltage</th> <th>Total Power Consumption</th> <th>Device Power Consumption</th> <th>PoE Budget</th> <th>Boost Efficiency</th> </tr> </thead> <tbody> <tr> <td>12VDC</td> <td>34.2W</td> <td>3.9W</td> <td>30W</td> <td>99.0%</td> </tr> <tr> <td>24VDC</td> <td>34.7W</td> <td>4.4W</td> <td>30W</td> <td>99.0%</td> </tr> <tr> <td>48VDC</td> <td>35.4W</td> <td>4.7W</td> <td>30W</td> <td>97.7%</td> </tr> </tbody> </table>	Power consumption & Boost efficiency					Input Voltage	Total Power Consumption	Device Power Consumption	PoE Budget	Boost Efficiency	12VDC	34.2W	3.9W	30W	99.0%	24VDC	34.7W	4.4W	30W	99.0%	48VDC	35.4W	4.7W	30W	97.7%
Power consumption & Boost efficiency																										
Input Voltage	Total Power Consumption	Device Power Consumption	PoE Budget	Boost Efficiency																						
12VDC	34.2W	3.9W	30W	99.0%																						
24VDC	34.7W	4.4W	30W	99.0%																						
48VDC	35.4W	4.7W	30W	97.7%																						
Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC																									
Removable Terminal Block	Provides 2 redundant power, alarm relay contact, 6 Pin																									

Operating Humidity	5%~95% (Non-condensing)
Operating Temperature	-20°C ~ 75°C (IMC-1000S-PHE12)
Storage Temperature	-40°C ~ 85°C
Housing	Rugged Metal, IP30 Protection and fanless
Dimensions	106 x 38.6 x 142 mm (D x W x H)
Weight	650g
Installation	DIN Rail mounting, or wall mounting (Optional)
MTBF	881,372 Hours MIL-HDBK-217
Warranty	5 years
Certification	
EMC	CE
EMI	FCC Part 15 Subpart B Class A, CE
Railway Traffic	EN50121-4

Immunity for Heavy Industrial environment	EN 61000-6-2
Emission for Heavy industrial environment	EN 61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (EFT) Level 3, Criteria A EN 61000-4-5 (Surge) Level 3, Criteria B EN 61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF) Field strength 300A/m Criteria A
Safety	UL60950-1 (pending)
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

Application





Figure 1 : IMC-1000S-PH12 Industrial PoE Transmission



- Regulated PoE output voltage (55VDC) to stabilize PoE device
- Guarantee delivery PoE power distance to 100 meters
- Wide range input power 24/48VDC (20~57VDC)
- Built-in very high efficiency (94~97%) to boost PoE output voltage

Figure 2 : High efficiency boost technology for PoE





Figure 3 : Remote PD Reset Application


Dimensions



Ordering Information

Model Name	RJ45 UTP	Fiber	PoE Port		Power Input	Certification				Operating Temperature
	10/100/1000 Base-T	Dual Speed 100/1000Base-X	IEEE802.3at (PSE)	Power Budget	Redundant	Railway EN50121-4	EN61000-6-2 EN61000-6-4	CE	FCC	
IMC-1000S-PHE12	1	1 SFP	1	30W	12/24/48VDC	V	V	V	V	-20~75°C

Model Naming Rule



Optional Accessories

Wall mount kit accessories


IND-WMK02 Wall Mount kit for Industrial product, 184 x 50mm

Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with the IMC-1000S-PH12 product for guaranteed compatibility and performance. The best performance can be guaranteed even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheet for more details and more items.)

ISFP-M7000-85-D(E)	Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDML, -10~70°C (-40~85°C)
ISFP-S7020-31-D(E)	Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDML, -10~70°C (-40~85°C)
ISFP-T7T00-00-(E)	Industrial SFP 1000Base-T UTP 100meter, -10~70°C (-40~85°C)
ISFP-M5002-31-D(E)	Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDML, -10~70°C (-40~85°C)
ISFP-S5030-31-D(E)	Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDML, -10~70°C (-40~85°C)

SFP Naming Rule



Package List

- IMC-1000S-PH12 device
- Quickly installation guide
- Din Rail bracket with screws
- Terminal block
- Protective caps for SFP ports