

FRM220-1000TS

1000Base-T to 1000Base-X SFP Media Converter



The FRM220-1000TS is a transparent Gigabit Ethernet 1000Base-T to 1000Base-SX/LX SFP converter with very low latency. They are managed (when installed in FRM220 with NMC) or non-managed stand-alone media converters, which give you the options to choose from a wide range of industry standard SFP modules with LC connectors. SFPs in multi-mode and single mode types are available as well as BiDi which allows bi-directional transmissions using only a single fiber cable. Because they are completely transparent to Ethernet packets, they are able to support any size frames, including undersized or jumbo packets (>9K bytes). LED indicators signal the power status of the converter, UTP port speed, Link, and duplex status, FX port Link and duplex status.


Features

- 1000Base-T to 1000Base-SX/LX
- Network management via terminal or SNMP in FRM220 chassis
- Auto-negotiation or force mode
- Auto MDI/MDIX
- Forward > 9K bytes packets
- Supports Link Fault Pass Through (LFP) function
- Auto Laser Shutdown (ALS)
- Protocol Transparent

Specifications

Optical Interface	Connector	SFP LC	Standard	IEEE 802.3ab		
	Data rate	1000Mbps		Indications	LED (Power, FX-Link, FX Duplex, TX-SPD, TX-Duplex, TX-Link)	
	Duplex mode	Full duplex			Power Input	Card : 12VDC Standalone : AC, DC options
	Fiber	MM 50/125µm, 62.5/125µm SM 9/125µm		Power Consumption		< 12W
	Distance	MM 550m, 2km, SM15/30/50/80/120km WDM 20/40/60km				Dimensions
Wavelength	MM 1310nm, SM 1310,1550nm WDM 1310Tx/1550Rx (type A) 1550Tx/1310Rx (type B)	Weight	120g			
Electrical Interface	Connector	RJ45	Temperature	0 ~ 50°C (Operating), -10 ~ 70°C (Storage)		
	Data rate	1000Mbps	Humidity	10 ~ 90% non-condensing		
	Duplex mode	Full duplex	Certification	CE, FCC, LVD		
	Cable	10Base-T Cat.3, 4, 5, UTP	MTBF	65,000 hrs (25°C)		

Application



Ordering Information

Model Name	Description
FRM220-1000TS	1000Base-T to 1000Base-X SFP media converter (Optional SFP)

Note: This Card is suitable for use in CH01 standalone chassis