

FMUX1001

Modularized 16E1/T1 + 4x GbE Managed Fiber Multiplexer

FMUX101

Modularized 16E1/T1 + 4x FE Managed Fiber Multiplexer



The FMUX1001/FMUX101 is a 1U, 19" rack mountable, PDH fiber optic multiplexer that transmits up to 16 channels plus a 10/100/1000Base-T (FMUX1001) / 10/100Base-TX (FMUX101) Ethernet channel over a single fiber optic link. The FMUX1001/FMUX101 chassis supports redundant power and hot swappable design. The AC supplies operate from 100~240VAC while DC supplies operate from 18~60VDC. From the rear of the chassis, one to four hot swappable quad E1 or T1 line cards, serial data communications (V.35, X.21, RS-530) or FXO/FXS voice cards are supported. The standard FMUX1001 configuration may be viewed or set via the front panel LCD/menu keys, serial VT-100 terminal connection, Telnet, web HTTP or SNMP.

Features


- 1U, 19 (23)" 4-slot chassis
- 16 E1 (2.048Mb/s) Multiplexer with 100/1000Mbps Ethernet and RS-232 data (async) Interface (FMUX1001)
- 16 E1 (2.048Mb/s) Multiplexer with 10/100Mbps Ethernet and RS-232 data (async) Interface (FMUX101)
- RS-232 port for system console
- One alarm output port, one Order Wire port
- 4x 10/100/1000Base-T Ethernet ports (FMUX1001)
- 4x 10/100/1000Base-T Ethernet ports (FMUX101)
- SNMP management
- LCD plus menu keys for local configuration
- Port based VLAN, tag based VLAN & bandwidth control
- Telnet and web based remote configuration
- 2 plug-in SFP slot for optical SFP module
- Forward 1024K byte packets on Ethernet port

Specifications

Optical Interface	Connector	SFP - LC	Standards	E1:ITU-T, T1:ITU-T, AT&T, ANSI, Ethernet: IEEE802.3x				
	Data rate	1.25G (FMUX1001), 155M (FMUX101)		Indications	PWR, Alarm, Phone, ACO, Port, Channels			
	Bit Error Rate	Less than 10 ⁻¹¹			Power Input	AC module IN : AC 90 ~ 264V, Out : DC 12V DC module IN : DC 18 ~ 72V, Out : DC 12V		
	Fiber	MM 62.2/125µm, 50/125µm SM 9/125µm				Power Consumption	< 25W	
	Distance	MM 2km. SM 15/30/50/80/120km WDM 20/40/60/80km					Dimensions	250 x 438 x 43mm (D x W x H)
	Wavelength	1310, 1550nm						Weight
Electrical Interface	Console, SNMP	RJ45	Temperature					
	Ethernet	4x RJ45		Humidity				
	Alarm	RJ45			Certification			
						MTBF		

Application

Remote 3G BTS connection Application



-Related Products: FMUX101, FMUX1600/160, FMUX04E (16x E1/T1 + 4x GbE/FE FOM, 4E1/T1 + 3x FE FOM)