



FRM220A-GSW/SNMP-10G

10G uplink Ethernet Aggregation Switch Card

The FRM220A-GSW/SNMP-10G is the next generation management module card for the FRM220A chassis. This card is built with Gigabit Ethernet interfaces to connect the backplane with each slot of FRM220A chassis. Twenty ports supply each slot of the 2U 20-slot chassis with an electrical gigabit Ethernet uplink with a remaining three electrical gigabit ports accessible via the rear of the chassis. The additional four uplink SFP ports provide 1G/10G Ethernet connections. All eight ports (4x GE+ 4x 1G/10G) are usable without restrictions for uplink aggregate to the Ethernet Metropolitan Area Network (E-MAN). The FRM220A-GSW/SNMP-10G card transmits Ethernet between the subscriber equipment (bridge/modem or network interface card) and the E-MAN. The card provides a user-networking interface with Ethernet packets. This card is capable of providing high bandwidth for assembling Ethernet traffic. The FRM220A-GSW/SNMP-10G card is not only the system aggregate/trunk module, but also the system's control module, providing serial console, SSHv2, SNMP (v1, v2c, v3) and Web GUI Management functions.

Features

- Provides chassis aggregation via 4x 1G/10Gigabit Base-X SFP/ SFP+ uplink slots
- Supports IEEE 802.1p HW based 8 priority queues and L2~L4 QoS functions
- Supports IPv6 management
- Fiber optical ports supports Ring topology
- Built-in gigabit Ethernet interface to link with each slot of FRM220A chassis
- Provides Console, Web (https), Telnet, SSHv2, SNMP(V1, V2c, V3) management interface
- Supports IEEE 802.1D/802.1w/802.1s for ring protection on the trunk interfaces
- Supports IEEE 802.1Q tagged VLAN and IEEE 802.1ad Q-in-Q application

Specifications

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------|
| Trunk Interface | 4x 1G/10G Base-X SFP + 4x 10/100/1000Base-T RJ45 switch trunk card Supports full-duplex mode for 1G/10G Mbps |
| Capacity | Supports up to 20 service cards |
| Temperature | 0~60°C (Operating), -10~70°C (Storage) |
| Humidity | 5~90% non-condensing |
| Certification | CE, FCC, RoHS compliant |

| | | |
|--------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Management | In-band management | Provides all system Web GUI functions software updates and management system interaction through Ethernet trunk port |
| | Out-band management | Supports Console, Web (https), Telnet, SSHv2, SNMP (v1.v2.v3), EMS |
| Indications | PWR, FAN, Alarm, STK | |
| Dimensions | 142 x 200 x 26 mm (D x W x H) | |
| Weight | 0.5kg | |
| MTBF | 65,000 hrs | |

Ordering Information

| Model Name | Type | Description |
|----------------------|---------|------------------------------------------------------------------------------------|
| FRM220A-CH20 | Chassis | 2U 20-Slot rack mount chassis with 20 line console blank plate |
| FRM220A-GSW/SNMP-10G | Card | 10G Ethernet Aggregate switch card supports web, telnet, SNMP management interface |
| FRM220A-AC | Power | Chassis power module 100 ~ 240 VAC, IEC connector |
| FRM220A-DC24 | Power | Chassis power module 18 ~ 36 VDC, 3 pin terminal block |
| FRM220A-DC48 | Power | Chassis power module 36 ~ 72 VDC, 3 pin terminal block |

FRM220A –
Example: FRM220A – CH20

FRM220A – / –
Example: FRM220A – GSW/SNMP-10G